

Linear Fixture Lighting Made Easy

Linear fixtures are sized to fit standard cabinet widths and come in several profile options. Use the **Angled Profile (P3)** under cabinets, inside cabinets, or in the toe kick to angle light where it's needed. Use the **Flat Profile (P7)** under cabinets to illuminate the workspace directly below. Use the **Recessed Profile (PX)** under cabinets or shelves for a flush, sleek finish. Use the multi-purpose **Dual-Mount Profile (PD)** for surface- or recess-mounted applications. Use the **Premium Flat Profile (PF)** for a sleek, finished look under cabinets.

The Accent, Standard, High, and Higher Output Single-White fixtures have color temperature options for Soft White (3000K) and Cool White (4000K).



225 lm./ft. Standard Output Single-White Fixture Example *Angled Profile, 12V*

Profile Option

L V 2 P 3 1 2 V 0 9 - 0 3 W 3



400 lm./ft. High Output Single-White Fixture Example *Flat Profile, 24V*

Profile Option

L S 4 P 7 2 4 V 2 1 - 0 6 W 4



600 lm./ft. Higher Output Single-White Fixture Example *Premium Flat Profile, 24V*

Profile Option

L S 6 P F 2 4 V 4 2 B 1 8 W 4



600 lm./ft. Higher Output Single-White Fixture Example *Dual-Mount Profile, 24V*

Profile Option

L S 6 P D 2 4 V 4 8 - 2 0 W 3



600 lm./ft. Higher Output Single-White Fixture Example *Recessed Profile, 24V*

Profile Option

L S 6 P X 2 4 V 4 2 - 1 8 W 4



Looking for tunable-white linear fixtures?

Scan the QR code or visit <https://delivr.com/2qe7m> for more information.

Single-White Linear Fixtures

09" Cabinet Runs	Angled Profile	Flat Profile	Recessed Profile	Dual-Mount Profile	Premium Flat Profile
120 lm./ft. Accent Output Fixtures (12V)	LR1 P3 12V09-02WTemp	LR1 P7 12V09-02WTemp	LR1 PX 12V09-02WTemp	—	—
225 lm./ft. Standard Output Fixtures (12V)	LV2 P3 12V09-03WTemp	LV2 P7 12V09-03WTemp	LV2 PX 12V09-03WTemp	—	—
120 lm./ft. Accent Output Fixtures (24)	LR1 P3 24V09-02WTemp	LR1 P7 24V09-02WTemp	LR1 PX 24V09-02WTemp	LS1 PD 24V09-01WTemp	—
225 lm./ft. Standard Output Fixtures (24)	LV2 P3 24V09-03WTemp	LV2 P7 24V09-03WTemp	LV2 PX 24V09-03WTemp	LS2 PD 24V09-01WTemp	—
400 lm./ft. High Output Fixtures (24)	LS4 P3 24V09-03WTemp	LS4 P7 24V09-03WTemp	LS4 PX 24V09-03WTemp	LS4 PD 24V09-02WTemp	—
600 lm./ft. Higher Output Fixtures (24)	LS6 P3 24V09-03WTemp	LS6 P7 24V09-03WTemp	LS6 PX 24V09-03WTemp	LS6 PD 24V09-02WTemp	LS6 PF 24V09Color03WTemp
Accent Output (12V), Standard, High, & Higher Output (12V & 24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 6-5/8", PD Profile: 6" Accent Output (24V) Single-White Fixture Length: P3, P7, & PX Profiles: 4-11/16", PD Profile: 6"					

12" Cabinet Runs	Angled Profile	Flat Profile	Recessed Profile	Dual-Mount Profile	Premium Flat Profile
120 lm./ft. Accent Output Fixtures (12V)	LR1 P3 12V12-02WTemp	LR1 P7 12V12-02WTemp	LR1 PX 12V12-02WTemp	—	—
225 lm./ft. Standard Output Fixtures (12V)	LV2 P3 12V12-03WTemp	LV2 P7 12V12-03WTemp	LV2 PX 12V12-03WTemp	—	—
120 lm./ft. Accent Output Fixtures (24)	LR1 P3 24V12-02WTemp	LR1 P7 24V12-02WTemp	LR1 PX 24V12-02WTemp	LS1 PD 24V12-01WTemp	—
225 lm./ft. Standard Output Fixtures (24)	LV2 P3 24V12-03WTemp	LV2 P7 24V12-03WTemp	LV2 PX 24V12-03WTemp	LS2 PD 24V12-02WTemp	—
400 lm./ft. High Output Fixtures (24)	LS4 P3 24V12-03WTemp	LS4 P7 24V12-03WTemp	LS4 PX 24V12-03WTemp	LS4 PD 24V12-02WTemp	—
600 lm./ft. Higher Output Fixtures (24)	LS6 P3 24V12-04WTemp	LS6 P7 24V12-04WTemp	LS6 PX 24V12-04WTemp	LS6 PD 24V12-03WTemp	LS6 PF 24V12Color04WTemp
Accent Output (12V), Standard, High, & Higher Output (12V & 24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 8-1/8", PD Profile: 8" Accent Output (24V) Single-White Fixture Length: P3, P7, & PX Profiles: 8-1/8", PD Profile: 9-15/16"					

Single-White Linear Fixtures

15" Cabinet Runs	Angled Profile	Flat Profile	Recessed Profile	Dual-Mount Profile	Premium Flat Profile
120 lm./ft. Accent Output Fixtures (12V)	LR1 P3 12V15-02WTemp	LR1 P7 12V15-02WTemp	LR1 PX 12V15-02WTemp	—	—
225 lm./ft. Standard Output Fixtures (12V)	LV2 P3 12V15-04WTemp	LV2 P7 12V15-04WTemp	LV2 PX 12V15-04WTemp	—	—
120 lm./ft. Accent Output Fixtures (24)	LR1 P3 24V15-02WTemp	LR1 P7 24V15-02WTemp	LR1 PX 24V15-02WTemp	LS1 PD 24V15-01WTemp	—
225 lm./ft. Standard Output Fixtures (24)	LV2 P3 24V15-04WTemp	LV2 P7 24V15-04WTemp	LV2 PX 24V15-04WTemp	LS2 PD 24V15-03WTemp	—
400 lm./ft. High Output Fixtures (24)	LS4 P3 24V15-04WTemp	LS4 P7 24V15-04WTemp	LS4 PX 24V15-04WTemp	LS4 PD 24V15-03WTemp	—
600 lm./ft. Higher Output Fixtures (24)	LS6 P3 24V15-06WTemp	LS6 P7 24V15-06WTemp	LS6 PX 24V15-06WTemp	LS6 PD 24V15-05WTemp	LS6 PF 24V15Color06WTemp
Accent Output (12V), Standard, High, & Higher Output (12V & 24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 12-9/16", PD Profile: 11-15/16" Accent Output (24V) Single-White Fixture Length: P3, P7, & PX Profiles: 12-9/16", PD Profile: 9-15/16"					

18" Cabinet Runs	Angled Profile	Flat Profile	Recessed Profile	Dual-Mount Profile	Premium Flat Profile
120 lm./ft. Accent Output Fixtures (12V)	LR1 P3 12V18-03WTemp	LR1 P7 12V18-03WTemp	LR1 PX 12V18-03WTemp	—	—
225 lm./ft. Standard Output Fixtures (12V)	LV2 P3 12V18-05WTemp	LV2 P7 12V18-05WTemp	LV2 PX 12V18-04WTemp	—	—
120 lm./ft. Accent Output Fixtures (24)	LR1 P3 24V18-03WTemp	LR1 P7 24V18-05WTemp	LR1 PX 24V18-03WTemp	LS1 PD 24V18-02WTemp	—
225 lm./ft. Standard Output Fixtures (24)	LV2 P3 24V18-05WTemp	LV2 P7 24V18-05WTemp	LV2 PX 24V18-04WTemp	LS2 PD 24V18-04WTemp	—
400 lm./ft. High Output Fixtures (24)	LS4 P3 24V18-05WTemp	LS4 P7 24V18-05WTemp	LS4 PX 24V18-04WTemp	LS4 PD 24V18-05WTemp	—
600 lm./ft. Higher Output Fixtures (24)	LS6 P3 24V18-07WTemp	LS6 P7 24V18-07WTemp	LS6 PX 24V18-06WTemp	LS6 PD 24V18-07WTemp	LS6 PF 24V18Color07WTemp
Accent Output (12V), Standard, High, & Higher Output (12V & 24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 14-1/2", PD Profile: 15-7/8" Accent Output (24V) Single-White Fixture Length: P3, P7, & PX Profiles: 12-9/16", PD Profile: 13-7/8"					

Single-White Linear Fixtures

21" Cabinet Runs	Angled Profile	Flat Profile	Recessed Profile	Dual-Mount Profile	Premium Flat Profile
120 lm./ft. Accent Output Fixtures (12V)	LR1 P3 12V21-03WTemp	LR1 P7 12V21-03WTemp	LR1 PX 12V21-03WTemp	—	—
225 lm./ft. Standard Output Fixtures (12V)	LV2 P3 12V21-05WTemp	LV2 P7 12V21-05WTemp	LV2 PX 12V21-05WTemp	—	—
120 lm./ft. Accent Output Fixtures (24)	LR1 P3 24V21-03WTemp	LR1 P7 24V21-03WTemp	LR1 PX 24V21-03WTemp	LS1 PD 24V21-02WTemp	—
225 lm./ft. Standard Output Fixtures (24)	LV2 P3 24V21-05WTemp	LV2 P7 24V21-05WTemp	LV2 PX 24V21-05WTemp	LS2 PD 24V21-04WTemp	—
400 lm./ft. High Output Fixtures (24)	LS4 P3 24V21-06WTemp	LS4 P7 24V21-05WTemp	LS4 PX 24V21-06WTemp	LS4 PD 24V21-05WTemp	—
600 lm./ft. Higher Output Fixtures (24)	LS6 P3 24V21-09WTemp	LS6 P7 24V21-07WTemp	LS6 PX 24V21-09WTemp	LS6 PD 24V21-08WTemp	LS6 PF 24V21Color09WTemp
Accent Output (12V), Standard, High, & Higher Output (12V & 24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 18-7/16", PD Profile: 17-13/16" Accent Output (24V) Single-White Fixture Length: P3, P7, & PX Profiles: 4-11/16", PD Profile: 6"					

24" Cabinet Runs	Angled Profile	Flat Profile	Recessed Profile	Dual-Mount Profile	Premium Flat Profile
120 lm./ft. Accent Output Fixtures (12V)	LR1 P3 12V24-03WTemp	LR1 P7 12V24-03WTemp	LR1 PX 12V24-03WTemp	—	—
225 lm./ft. Standard Output Fixtures (12V)	LV2 P3 12V24-06WTemp	LV2 P7 12V24-06WTemp	LV2 PX 12V24-06WTemp	—	—
120 lm./ft. Accent Output Fixtures (24)	LR1 P3 24V24-03WTemp	LR1 P7 24V24-03WTemp	LR1 PX 24V24-03WTemp	LS1 PD 24V24-03WTemp	—
225 lm./ft. Standard Output Fixtures (24)	LV2 P3 24V24-06WTemp	LV2 P7 24V24-06WTemp	LV2 PX 24V24-06WTemp	LS2 PD 24V24-05WTemp	—
400 lm./ft. High Output Fixtures (24)	LS4 P3 24V24-07WTemp	LS4 P7 24V24-07WTemp	LS4 PX 24V24-07WTemp	LS4 PD 24V24-06WTemp	—
600 lm./ft. Higher Output Fixtures (24)	LS6 P3 24V24-10WTemp	LS6 P7 24V24-10WTemp	LS6 PX 24V24-10WTemp	LS6 PD 24V24-09WTemp	LS6 PF 24V24Color10WTemp
Accent Output (12V), Standard, High, & Higher Output (12V & 24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 20-7/16", PD Profile: 21-3/4" Accent Output (24V) Single-White Fixture Length: P3, P7, & PX Profiles: 4-11/16", PD Profile: 21-3/4"					

Single-White Linear Fixtures

27" Cabinet Runs	Angled Profile	Flat Profile	Recessed Profile	Dual-Mount Profile	Premium Flat Profile
120 lm./ft. Accent Output Fixtures (12V)	LR1 P3 12V27-04WTemp	LR1 P7 12V27-04WTemp	LR1 PX 12V27-04WTemp	—	—
225 lm./ft. Standard Output Fixtures (12V)	LV2 P3 12V27-07WTemp	LV2 P7 12V27-07WTemp	LV2 PX 12V27-07WTemp	—	—
120 lm./ft. Accent Output Fixtures (24)	LR1 P3 24V27-04WTemp	LR1 P7 24V27-04WTemp	LR1 PX 24V27-04WTemp	LS1 PD 24V27-03WTemp	—
225 lm./ft. Standard Output Fixtures (24)	LV2 P3 24V27-07WTemp	LV2 P7 24V27-07WTemp	LV2 PX 24V27-07WTemp	LS2 PD 24V27-05WTemp	—
400 lm./ft. High Output Fixtures (24)	LS4 P3 24V27-08WTemp	LS4 P7 24V27-08WTemp	LS4 PX 24V27-08WTemp	LS4 PD 24V27-07WTemp	—
600 lm./ft. Higher Output Fixtures (24)	LS6 P3 24V27-12WTemp	LS6 P7 24V27-12WTemp	LS6 PX 24V27-12WTemp	LS6 PD 24V27-10WTemp	LS6 PF 24V27Color11WTemp
Accent Output (12V), Standard, High, & Higher Output (12V & 24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 24-3/8" , PD Profile: 23-3/4" Accent Output (24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 24-3/8", PD Profile: 21-3/4"					

30" Cabinet Runs	Angled Profile	Flat Profile	Recessed Profile	Dual-Mount Profile	Premium Flat Profile
120 lm./ft. Accent Output Fixtures (12V)	LR1 P3 12V30-04WTemp	LR1 P7 12V30-04WTemp	LR1 PX 12V30-04WTemp	—	—
225 lm./ft. Standard Output Fixtures (12V)	LV2 P3 12V30-07WTemp	LV2 P7 12V30-07WTemp	LV2 PX 12V30-07WTemp	—	—
120 lm./ft. Accent Output Fixtures (24)	LR1 P3 24V30-04WTemp	LR1 P7 24V30-04WTemp	LR1 PX 24V30-04WTemp	LS1 PD 24V30-03WTemp	—
225 lm./ft. Standard Output Fixtures (24)	LV2 P3 24V30-07WTemp	LV2 P7 24V30-07WTemp	LV2 PX 24V30-07WTemp	LS2 PD 24V30-06WTemp	—
400 lm./ft. High Output Fixtures (24)	LS4 P3 24V30-08WTemp	LS4 P7 24V30-08WTemp	LS4 PX 24V30-08WTemp	LS4 PD 24V30-08WTemp	—
600 lm./ft. Higher Output Fixtures (24)	LS6 P3 24V30-12WTemp	LS6 P7 24V30-12WTemp	LS6 PX 24V30-12WTemp	LS6 PD 24V30-12WTemp	LS6 PF 24V30Color13WTemp
Accent Output (12V), Standard, High, & Higher Output (12V & 24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 26-5/16", PD Profile: 27-11/16" Accent Output (24V) Single-White Fixture Length: P3, P7, & PX Profiles: 24-3/8", PD Profile: 25-11/16"					

Single-White Linear Fixtures

33" Cabinet Runs	Angled Profile	Flat Profile	Recessed Profile	Dual-Mount Profile	Premium Flat Profile
120 lm./ft. Accent Output Fixtures (12V)	LR1 P3 12V33-05WTemp	LR1 P7 12V33-05WTemp	LR1 PX 12V33-05WTemp	—	—
225 lm./ft. Standard Output Fixtures (12V)	LV2 P3 12V33-08WTemp	LV2 P7 12V33-08WTemp	LV2 PX 12V33-08WTemp	—	—
120 lm./ft. Accent Output Fixtures (24)	LR1 P3 24V33-05WTemp	LR1 P7 24V33-05WTemp	LR1 PX 24V33-05WTemp	LS1 PD 24V33-04WTemp	—
225 lm./ft. Standard Output Fixtures (24)	LV2 P3 24V33-08WTemp	LV2 P7 24V33-08WTemp	LV2 PX 24V33-08WTemp	LS2 PD 24V33-07WTemp	—
400 lm./ft. High Output Fixtures (24)	LS4 P3 24V33-10WTemp	LS4 P7 24V33-10WTemp	LS4 PX 24V33-10WTemp	LS4 PD 24V33-09WTemp	—
600 lm./ft. Higher Output Fixtures (24)	LS6 P3 24V33-14WTemp	LS6 P7 24V33-14WTemp	LS6 PX 24V33-14WTemp	LS6 PD 24V33-13WTemp	LS6 PF 24V33Color14WTemp
Accent Output (12V), Standard, High, & Higher Output (12V & 24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 30-1/4", PD Profile: 29-5/8" Accent Output (24V) Single-White Fixture Length: P3, P7, & PX Profiles: 28-5/16", PD Profile: 29-5/8"					

36" Cabinet Runs	Angled Profile	Flat Profile	Recessed Profile	Dual-Mount Profile	Premium Flat Profile
120 lm./ft. Accent Output Fixtures (12V)	LR1 P3 12V36-05WTemp	LR1 P7 12V36-05WTemp	LR1 PX 12V36-05WTemp	—	—
225 lm./ft. Standard Output Fixtures (12V)	LV2 P3 12V36-09WTemp	LV2 P7 12V36-09WTemp	LV2 PX 12V36-09WTemp	—	—
120 lm./ft. Accent Output Fixtures (24)	LR1 P3 24V36-05WTemp	LR1 P7 24V36-05WTemp	LR1 PX 24V36-05WTemp	LS1 PD 24V36-04WTemp	—
225 lm./ft. Standard Output Fixtures (24)	LV2 P3 24V36-09WTemp	LV2 P7 24V36-09WTemp	LV2 PX 24V36-09WTemp	LS2 PD 24V36-08WTemp	—
400 lm./ft. High Output Fixtures (24)	LS4 P3 24V36-10WTemp	LS4 P7 24V36-10WTemp	LS4 PX 24V36-10WTemp	LS4 PD 24V36-10WTemp	—
600 lm./ft. Higher Output Fixtures (24)	LS6 P3 24V36-15WTemp	LS6 P7 24V36-15WTemp	LS6 PX 24V36-15WTemp	LS6 PD 24V36-15WTemp	LS6 PF 24V36Color15WTemp
Accent Output (12V), Standard, High, & Higher Output (12V & 24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 32-1/4", PD Profile: 33-9/16" Accent Output (24V) Single-White Fixture Length: P3, P7, & PX Profiles: 32-1/4", PD Profile: 33-9/16"					

Single-White Linear Fixtures

39" Cabinet Runs	Angled Profile	Flat Profile	Recessed Profile	Dual-Mount Profile	Premium Flat Profile
120 lm./ft. Accent Output Fixtures (12V)	LR1 P3 12V39-05WTemp	LR1 P7 12V39-05WTemp	LR1 PX 12V39-05WTemp	—	—
225 lm./ft. Standard Output Fixtures (12V)	LV2 P3 12V39-10WTemp	LV2 P7 12V39-10WTemp	LV2 PX 12V39-010WTemp	—	—
120 lm./ft. Accent Output Fixtures (24)	LR1 P3 24V39-05WTemp	LR1 P7 24V39-05WTemp	LR1 PX 24V39-05WTemp	LS1 PD 24V39-04WTemp	—
225 lm./ft. Standard Output Fixtures (24)	LV2 P3 24V39-10WTemp	LV2 P7 24V39-10WTemp	LV2 PX 24V39-10WTemp	LS2 PD 24V39-08WTemp	—
400 lm./ft. High Output Fixtures (24)	LS4 P3 24V39-11WTemp	LS4 P7 24V39-11WTemp	LS4 PX 24V39-11WTemp	LS4 PD 24V39-10WTemp	—
600 lm./ft. Higher Output Fixtures (24)	LS6 P3 24V39-17WTemp	LS6 P7 24V39-17WTemp	LS6 PX 24V39-17WTemp	LS6 PD 24V39-15WTemp	LS6 PF 24V39Color17WTemp
Accent Output (12V), Standard, High, & Higher Output (12V & 24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 36-3/16", PD Profile: 35-9/16" Accent Output (24V) Single-White Fixture Length: P3, P7, & PX Profiles: 36-3/16", PD Profile: 33-9/16"					

42" Cabinet Runs	Angled Profile	Flat Profile	Recessed Profile	Dual-Mount Profile	Premium Flat Profile
120 lm./ft. Accent Output Fixtures (12V)	LR1 P3 12V42-06WTemp	LR1 P7 12V42-06WTemp	LR1 PX 12V42-06WTemp	—	—
225 lm./ft. Standard Output Fixtures (12V)	LV2 P3 12V42-10WTemp	LV2 P7 12V42-10WTemp	LV2 PX 12V42-10WTemp	—	—
120 lm./ft. Accent Output Fixtures (24)	LR1 P3 24V42-06WTemp	LR1 P7 24V42-6WTemp	LR1 PX 24V42-06WTemp	LS1 PD 24V42-05WTemp	—
225 lm./ft. Standard Output Fixtures (24)	LV2 P3 24V42-10WTemp	LV2 P7 24V42-10WTemp	LV2 PX 24V42-10WTemp	LS2 PD 24V42-09WTemp	—
400 lm./ft. High Output Fixtures (24)	LS4 P3 24V42-12WTemp	LS4 P7 24V42-11WTemp	LS4 PX 24V42-12WTemp	LS4 PD 24V42-12WTemp	—
600 lm./ft. Higher Output Fixtures (24)	LS6 P3 24V42-18WTemp	LS6 P7 24V42-17WTemp	LS6 PX 24V42-18WTemp	LS6 PD 24V42-17WTemp	LS6 PF 24V42Color18WTemp
Accent Output (12V), Standard, High, & Higher Output (12V & 24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 38-1/8", PD Profile: 39-1/2" Accent Output (24V) Single-White Fixture Length: P3, P7, & PX Profiles: 36-3/16", PD Profile: 37-1/2"					

Single-White Linear Fixtures

45" Cabinet Runs	Angled Profile	Flat Profile	Recessed Profile	Dual-Mount Profile	Premium Flat Profile
120 lm./ft. Accent Output Fixtures (12V)	LR1 P3 12V45-06WTemp	LR1 P7 12V45-06WTemp	LR1 PX 12V45-06WTemp	—	—
225 lm./ft. Standard Output Fixtures (12V)	LV2 P3 12V45-11WTemp	LV2 P7 12V45-11WTemp	LV2 PX 12V45-11WTemp	—	—
120 lm./ft. Accent Output Fixtures (24)	LR1 P3 24V45-06WTemp	LR1 P7 24V45-06WTemp	LR1 PX 24V45-06WTemp	LS1 PD 24V45-05WTemp	—
225 lm./ft. Standard Output Fixtures (24)	LV2 P3 24V45-11WTemp	LV2 P7 24V45-11WTemp	LV2 PX 24V45-11WTemp	LS2 PD 24V45-09WTemp	—
400 lm./ft. High Output Fixtures (24)	LS4 P3 24V45-13WTemp	LS4 P7 24V45-13WTemp	LS4 PX 24V45-13WTemp	LS4 PD 24V45-12WTemp	—
600 lm./ft. Higher Output Fixtures (24)	LS6 P3 24V45-20WTemp	LS6 P7 24V45-14WTemp	LS6 PX 24V45-20WTemp	LS6 PD 24V45-18WTemp	LS6 PF 24V45Color19WTemp
Accent Output (12V), Standard, High, & Higher Output (12V & 24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 42-1/16", PD Profile: 41-7/16" Accent Output (24V) Single-White Fixture Length: P3, P7, & PX Profiles: 40-1/8", PD Profile: 41-7/16"					

48" Cabinet Runs	Angled Profile	Flat Profile	Recessed Profile	Dual-Mount Profile	Premium Flat Profile
120 lm./ft. Accent Output Fixtures (12V)	LR1 P3 12V48-06WTemp	LR1 P7 12V48-06WTemp	LR1 PX 12V48-06WTemp	—	—
225 lm./ft. Standard Output Fixtures (12V)	LV2 P3 12V48-12WTemp	LV2 P7 12V48-12WTemp	LV2 PX 12V48-12WTemp	—	—
120 lm./ft. Accent Output Fixtures (24)	LR1 P3 24V48-06WTemp	LR1 P7 24V48-06WTemp	LR1 PX 24V48-06WTemp	LS1 PD 24V48-06WTemp	—
225 lm./ft. Standard Output Fixtures (24)	LV2 P3 24V48-12WTemp	LV2 P7 24V48-12WTemp	LV2 PX 24V48-12WTemp	LS2 PD 24V48-10WTemp	—
400 lm./ft. High Output Fixtures (24)	LS4 P3 24V48-14WTemp	LS4 P7 24V48-14WTemp	LS4 PX 24V48-14WTemp	LS4 PD 24V48-13WTemp	—
600 lm./ft. Higher Output Fixtures (24)	LS6 P3 24V48-21WTemp	LS6 P7 24V48-21WTemp	LS6 PX 24V48-21WTemp	LS6 PD 24V48-20WTemp	LS6 PF 24V48Color21WTemp
Accent Output (12V), Standard, High, & Higher Output (12V & 24V) Single-White Fixture Length: P3, P7, PX, & PF Profiles: 44-1/16", PD Profile: 45-3/8" Accent Output (24V) Single-White Fixture Length: P3, P7, & PX Profiles: 44-1/16", PD Profile: 45-3/8"					