HR Series Comparison Undermount Slides

Series	USE58-500	USE58-300	USE58-50	USE58 Slide Kits	
Category	Synchronized Soft-close	EZ Open Heavy Duty	Standard Duty	Standard Duty	
Load rating*	100 lb Dynamic	100 lb Dynamic	100 lb Static	100 lb Static	
ANSI/BHMA lifecycle	50,000+	75,000+	50,000+	50,000+	
Protective spring cover: Prevents unwanted sawdust and granite dust from interfering with the soft-close mechanism	√	✓		✓	
Positive, no-worry drawer box engagement: Release clips effortlessly engage with the drawer	√	✓			
Soft-close	✓	✓	✓	✓	
EZ Open: Relaxed pull force for easy opening	✓	✓			
Slotted mounting holes for micro adjustments	√	✓			
Drawer Box Material Compatibility	1/2" - 5/8"	1/2" - 5/8"	1/2" - 5/8"	1/2" - 5/8"	
Lengths	12" - 24"	9" - 24"	12" - 21"	12" - 21"	

^{*}Static load rating is a non-moving weight test with the specified weight over 24 hours. Dynamic load rating is more robust and includes a moving weight test with a specific weight over a set number of cycles.

Undermount Release Clips

50/100/300 Series


6-Way Heavy Duty Adjustable Clip with Zinc Base



- Vertical adjustment: Up to 3 mm (1/8")
- Horizontal adjustment: +/- 2 mm (5/64")
- Depth adjustment: Up to 2.5 mm (3/32")
- For inset applications
- Heavy duty die cast zinc base
- US Patent 9,101,213 & 9,386,849 & 9,408,463 & 9,782,001

Description	Part Number	Ctn Qty
6-way adjustable clip with zinc base	US-CLIP-6WZ	200/ctn Packaged by pair (L/R)

4-Way Heavy Duty Adjustable Clip with Zinc Base



- Vertical adjustment: Up to 3 mm (1/8")
- Horizontal adjustment: +/- 2 mm (5/64")
- Heavy duty die cast zinc base

US Patent 9,101,213 & 9,408,463 & 9,782,001

Description	Part Number	Ctn Qty
4-way adjustable clip with zinc base	US-CLIP-4WZ	200/ctn Packaged by pair (L/R)

4-Way Standard Duty Adjustable Clip



- Vertical adjustment: Up to 3 mm (1/8")
- Horizontal adjustment: +/- 2 mm (5/64")

US Patent 9,101.213

Description	Part Number	Ctn Qty
4-way adjustable clip	US-CLIP-4W	200/ctn Packaged by pair (L/R)

2-Way Adjustable Narrow Clip



- Vertical adjustment: Up to 3 mm (1/8")
- Minimum drawer box width for 1/2" material = 4-1/2"
- Minimum drawer box width for 5/8" material = 4-7/8"

Description	Part Number	Ctn Qty
2-way adjustable clip	US-CLIP-NR	100/ctn Packaged by pair (L/R)

2-Way Adjustable Clip



- Vertical adjustment: Up to 3 mm (1/8")
- Die cast zinc base

Description	Part Number	Ctn Qty
2-way adjustable clip	US-CLIP-2W	200/ctn Packaged by pair (L/R)

DRAWER BOX MINIMUM WIDTH (VARIES BY CLIP)

	US-CLIP-6WZ	US-CLIP-4WZ	US-CLIP-4W	US-CLIP-2W	US-CLIP-NR
5/8" (16mm) material	7.25"	7.25"	7.25"	6.25"	4.875"
1/2" (13mm) material	7"	7"	7"	6"	4.5"

#6 x 5/8" pan head screw recommended for installation

Undermount Release Clips 500 Series

500 Series 6-Way Heavy Duty Adjustable Clip with Zinc Base



- Vertical adjustment: Up to 3 mm (1/8")
- Vertical adjustment: -/- 2 mm (5/64")
- Depth adjustment: Up to 3 mm (1/8")
- For inset applications
- Heavy duty die cast zinc base

US Patent 9,101,213 & 9,386,849 & 9,408,463 & 9,782,001 & 9,986,829

Description	Part Number	Ctn Qty
6-way adjustable clip with zinc base	USCLIP500-6WZ	200/ctn Packaged by pair (L/R)

500 Series 4-Way Heavy Duty Adjustable Clip with Zinc Base



- Vertical adjustment: Up to 3 mm (1/8")
- Horizontal adjustment: +/- 2 mm (5/64")
- Heavy duty die cast zinc base

US Patent 9,986,829

Description	Part Number	Ctn Qty
4-way adjustable clip with zinc base	USCLIP500-4WZ	200/ctn Packaged by pair (L/R)

500 Series 4-Way Standard Duty Adjustable Clip



- Vertical adjustment: Up to 3 mm (1/8")
- Horizontal adjustment: +/- 2 mm (5/64")

US Patent 9,386,849 & 9,408,463 & 9,782,001

Description	Part Number	Ctn Qty
4-way adjustable clip	USCLIP500-4W	200/ctn Packaged by pair (L/R)

4-Way Adjustable Clip for USE58-Kit Undermount Slides



- Vertical adjustment: Up to 3 mm (1/8")
- Horizontal adjustment: +/- 2 mm (5/64")

Description	Part Number	Ctn Qty
4-way adjustable clip	USE58-CLIP-4W	200/ctn Packaged by pair (L/R)

DRAWER BOX MINIMUM WIDTH (VARIES BY CLIP)

	USCLIP500-6WZ	USCLIP500-4WZ	USCLIP500-4W	USE58-CLIP-4W
5/8" (16mm) material	8.25"	8.25"	8.25"	8.25"
1/2" (13mm) material	8"	8"	8"	8"

#6 x 5/8" pan head screw recommended for installation